

| % Coverage | 3 mm Flake | 6 mm Flake |
|------------|---------------------|---------------------|
| 100 | 1.9 m ² | 2 m ² |
| 95 | 2 m ² | 2.1 m ² |
| 90 | 2.1 m ² | 2.2 m ² |
| 85 | 2.2 m ² | 2.3 m ² |
| 80 | 2.4 m ² | 2.5 m ² |
| 75 | 2.5 m ² | 2.7 m ² |
| 70 | 2.7 m ² | 2.9 m ² |
| 65 | 2.9 m ² | 3 m ² |
| 60 | 3.2 m ² | 3.3 m ² |
| 55 | 3.4 m ² | 3.6 m ² |
| 50 | 3.8 m ² | 4 m ² |
| 45 | 4.2 m ² | 4.4 m ² |
| 40 | 4.7 m ² | 5 m ² |
| 35 | 5.4 m ² | 5.7 m ² |
| 30 | 6.3 m ² | 6.7 m ² |
| 25 | 7.6 m ² | 8 m ² |
| 20 | 9.5 m ² | 10 m ² |
| 15 | 12.7 m ² | 13.3 m ² |
| 10 | 19 m ² | 20 m ² |
| 5 | 38 m ² | 40 m ² |

1 kg Coverage Rate

The above chart is to be used as a guide only. Coverage will vary depending on the experience of the installer and the method in which the INFUSION-FLAKE™ is broadcasted into the wet surface coating.

Surface conditions can also determine coverage rates, as well as environmental factors - especially when applied in exterior applications where a light breeze can account for a large wastage factor. As with all surface coating systems, a wastage factor should be equated into material consumption.

For a more specific INFUSION-FLAKE™ consumption estimation, visit the INFUSION-FLAKE™ systems page at www.alluvius.com.au